

---

**Searching for the Green Laboratory  
Building Exhaust**  
Presented to  
**Labs For the 21st Century  
Conference**

Presented by  
**Victor A. Neuman, PE**

**Strobic Air Corporation**  
A Subsidiary of Met-Pro Corporation

<b>STROBIC AIR CORPORATION</b>
--------------------------------

**The Green Lab Exhaust is:**

- **Safe for Humans**
- **Energy Conservative**
- **Minimizes Environmental Damage.**

<b>STROBIC AIR CORPORATION</b>
--------------------------------

---

## **SAFETY – The Problems**


- **An estimated 25% of Labs experience blow-back of toxic fumes for some winds.**
- **1992 OSHA Lab Standard says lab workers can see life-spans 10 years shorter.**



**STROBIC AIR CORPORATION**

## **Problems with Single hood-- Single Stack**

- **Low exit velocities (1,000-1,500 fpm) with down-wash probabilities.**
- **Lost fan motor creates back-flow through the stack and into lab.**
- **High Energy Use**



**STROBIC AIR CORPORATION**

---

## Is Your Stack Tall Enough?

- Height is Not Enough.
- Must have Flow Volume &
- Exit Velocity



STROBIC AIR CORPORATION

## The Basics for Green Exhausts

- Fans outside on Highest roof.
- Point the exhaust upwards, with minimum 10 height, no caps or goosenecks.
- Minimum exit velocity of 3,000 ft/min.
- Maximize Flow by Manifolding inside lab or adding in air at the roof.
- Treat exhaust or dilute it to increase human safety and to reduce environmental hazard.
- See ASHRAE 1999, Ch. 43.

STROBIC AIR CORPORATION

---

## Safety--Method Comparison

Example from a recent project:


Fans:

Strobic TS3L200B12  
Conventional  
Un-manifolded (1000cfm)

Halitsky dilution criteria  
requires **3 ppm** or lower air  
intake concentration for a 15  
cfm chemical release

**RATCLIFF & ASSOCIATES**


Michael A. Ratcliff, Ph.D., P.E.  
Stack Design and Airflow Around Buildings  
Laboratory Fume Hood Testing



**STROBIC AIR CORPORATION**

## ENERGY CONSERVATION

- Direct Drive eliminates belt losses and breakdowns.
- Optimum inlet/outlet design reduces pressure loss 30%.
- Use 2 large fans at high efficiency instead of 100 smaller fans.



**STROBIC AIR CORPORATION**

---

## **ENVIRONMENTAL IMPACT**

- **Where possible, Provide treatment system or scrubbers to remove hazards from airstream**
- **Use Dilution if no other treatment possible.**
- **Noise pollution should be considered.**
- **Consider Visual Impact.**

<b>STROBIC AIR CORPORATION</b>
--------------------------------